

Canonical Logic Programs are Succinctly Incomparable with Propositional Formulas*

Yuping Shen and Xishun Zhao[†]

Institute of Logic and Cognition,
Department of Philosophy,
Sun Yat-sen University,
510275 Guangzhou, P.R. China
{shyping, hsszxs}@mail.sysu.edu.cn

January 27, 2015

Abstract

Canonical (logic) programs (CP) refer to normal logic programs augmented with connective *not not*. In this paper we address the question of whether CP are *succinctly incomparable* with *propositional formulas* (PF). Our main result shows that the PARITY problem, which can be polynomially represented in PF but *only* has exponential representations in CP. In other words, PARITY *separates* PF from CP. Simply speaking, this means that exponential size blowup is generally inevitable when translating a set of formulas in PF into an equivalent program in CP (without introducing new variables). Furthermore, since it has been shown by Lifschitz and Razborov that there is also a problem that separates CP from PF (assuming $P \not\subseteq NC^1/poly$), it follows that CP and PF are indeed succinctly incomparable. From the view of the theory of computation, the above result may also be considered as the separation of two *models of computation*, i.e., we identify a language in $NC^1/poly$ which is not in the set of languages computable by polynomial size CP programs.

1 Introduction

The study of logic programs under answer set semantics, i.e., *answer set programming* (ASP) [15, 26, 5], has been an active area in artificial intelligence since the past decades. As a competing approach to SAT [4], ASP has been successfully applied in many fields like Planning, Commonsense Reasoning, Scheduling, etc.

*Extended version of a paper with the same name in KR2014.

[†]Corresponding Author.

The relationship between logic programs and *propositional formulas* (PF) gains a lot of attention in the literature. A well-known theorem shown by Lin & Zhao [29] gives a method for translating a *normal (logic) program* (LP) to a (logically) equivalent set of formulas in PF, without introducing additional variables. However, it has been observed that the translation may result in an exponential number of so-called *loop formulas* in the worst case. In 2006, Lifschitz and Razborov proved that such exponential blowup is generally inevitable, more precisely, they showed that (a variant of) the P-complete *problem* PATH has polynomial size representations in LP, however, it *cannot* be polynomially represented in PF (assuming $P \not\subseteq NC^1/poly$) [28]. In other words, we say PATH *separates* LP from PF.

As noted in [28], PF can be considered as a special case of (*nondisjunctive*) *nested programs* (NLP) [25], which is a general form of programs that subsumes LP and some other kinds of programs. Therefore, NLP is *stronger* than PF in terms of the *succinctness* criterion (or the “*comparative linguistics*” approach) proposed in [17]:

That is, we consider formalism *A* to be stronger than formalism *B* if and only if any knowledge base (KB) in *B* has an equivalent KB in *A* that is only polynomially longer, while there is a KB in *A* that can be translated to *B* only with an exponential blowup.

So the following footnote in [26] seems convincing at first glance:

...ASP appears to be stronger than SAT in the sense of the “comparative linguistics” approach to knowledge representation...

However, since ASP involves many kinds of programs, the above statement probably needs further clarification. Particularly, the so-called (*nondisjunctive*) *canonical programs* (CP)¹ [22, 25, 24], is a “minimal” form of ASP that is equally expressive as PF, but looks more likely *not* succinctly stronger. So a question naturally arises: *Does there exist a problem that separates CP from PF?* If there is such a problem, then CP and PF are *succinctly incomparable* (assuming $P \not\subseteq NC^1/poly$).

In this paper we address the question and give a *positive* answer. Our main result shows that the problem PARITY separates PF from CP. Simply speaking, this means an exponential size blowup is generally inevitable when translating a set of formulas in PF into an equivalent program in CP (without introducing new variables). The PARITY problem asks whether a binary string contains an odd number of 1’s, and it is well-known that (i) PARITY $\in NC^1/poly$, i.e., it has polynomial representations in PF² [3, 21], (ii) PARITY $\notin AC^0$, i.e., it cannot be represented by *polynomial* size boolean circuits with *constant depth* and *unbounded fan-in* [14, 20].

To show PARITY separates PF from CP, we provide a procedure that simplifies every PARITY program Π into a shorter, *loop-free* program Π' . By Lin-Zhao

¹Extends LP with connective *not not*.

² $NC^1/poly$ (or *non-uniform* NC^1) *exactly* contains languages computable (i.e., representable) by polynomial size propositional formulas.

Theorem (or the (generalized) *Fages Theorem* [11, 10, 33]), Π' is equivalent to its completion $Comp(\Pi')$, the latter is essentially a constant depth, unbounded fan-in circuit whose size is polynomially bounded by $|\Pi'|$. According to $PARITY \notin AC^0$, these circuits must be of exponential size, consequently, there are no polynomial size CP programs for PARITY.

From the view of the theory of computation, the above result may also be considered as the separation of two *models of computation* [31], i.e., we identify a language in $NC^1/poly$ which is not in the set of languages computable by polynomial size CP programs. Based on the observation, we point out more separation results on some classes of logic programs, e.g., PARITY separates logic programs with *cardinality constraints* and *choice rules* (CC) [32] from CP; assuming $P \not\subseteq NC^1/poly$, CP and *definite causal theories* (DT) [30, 16] are succinctly incomparable; *two-valued* programs (TV) [27] are strictly more succinct than CP and DT, etc.

The rest of the paper is organized as follows: Section 2 gives preliminaries to the semantics of canonical programs, the concepts of succinctness and the PARITY problem. In Section 3 we briefly review the notation of boolean circuit, the completion semantics and the Lin-Zhao theorem. Section 4 illustrates how to simply an arbitrary PARITY program to be loop-free and presents the main theorem. In Section 5 we discuss the importance of succinctness research and point out more results on a family of logic program classes. Conclusions are drawn in the last Section.

2 Background

2.1 Canonical Programs

The following notations are adopted from [25, 22]. A *rule element* e is defined as

$$e := \top \mid \perp \mid x \mid not\ x \mid not\ not\ x$$

in which $\top, \perp$ are 0-ary connectives, x is a (*boolean*) *variable* (or an *atom*) and *not* is a unary connective³. A (*nondisjunctive canonical*) *rule* is an expression of the form

$$H \leftarrow B \tag{1}$$

where the *head* H is either a variable or the connective $\perp$, and the *body* B is a finite set of rule elements. A *canonical program* (CP) Π is a finite set of rules, Π is *normal* if it contains no connectives *not not*. A normal program Π is *basic* if it contains no connectives *not*. The following is a canonical program:

$$\begin{aligned} x_1 &\leftarrow not\ not\ x_1, & x_3 &\leftarrow not\ x_1, not\ x_2, \\ x_2 &\leftarrow not\ not\ x_2, & x_3 &\leftarrow x_1, x_2. \end{aligned} \tag{2}$$

³According to [25], *not not not x* can be replaced by *not x*.

The *satisfaction relation* $\models$ between a set of variables I and a rule element is defined as follows:

- $I \models \top$ and $I \not\models \perp$,
- $I \models x$ iff $I \models \text{not not } x$ iff $x \in I$,
- $I \models \text{not } x$ iff $x \notin I$.

Say I satisfies a set of rule elements B if I satisfies each rule elements in B . We say I is *closed* under a program Π , if I is closed under every rule in Π , i.e., for each rule $H \leftarrow B \in \Pi$, $I \models H$ whenever $I \models B$. Let Π be a basic program, $Cn(\Pi)$ denotes the *minimal* set (in terms of inclusion) closed under Π , we say I is an *answer set* of Π if $I = Cn(\Pi)$. Note that a basic program has exactly one answer set.

The *reduct* Π^I of a canonical program Π w.r.t. I is a set of rules obtained from Π via: (i) Replacing each *not not* x with $\top$ if $I \models x$, and with $\perp$ otherwise; (ii) Replacing each *not* x with $\top$ if $I \not\models x$, and with $\perp$ otherwise. Observe that Π^I must be a basic program. We say I is an answer set of Π if $I = Cn(\Pi^I)$, i.e., I is an answer set of Π^I .

The following single rule canonical program Π :

$$x \leftarrow \text{not not } x \quad (3)$$

has two answer sets $\{x\}$ and $\emptyset$. To see this, check that $\Pi^{\{x\}}$ is $\{x \leftarrow \top\}$, whose only answer set is $\{x\}$. Similarly, $\Pi^\emptyset$ is $\{x \leftarrow \perp\}$, whose only answer set is $\emptyset$. For convenience, $\top$ in the body is often omitted.

For a set of rule elements B , define $var(B) = \{e \in B : e \text{ is a variable}\}$. E.g., $var(\{x_1, \text{not } x_2, \text{not not } x_3\}) = \{x_1\}$. Let Π be a program, by $var(\Pi)$ we denote the set of all variables involved in Π and by $Ans(\Pi)$ we denote the set of all answer sets of Π . E.g., let Π be program (2), then $var(\Pi) = \{x_1, x_2, x_3\}$ and $Ans(\Pi) = \{\{x_1, x_2, x_3\}, \{x_1\}, \{x_2\}, \{x_3\}\}$. As a convention, by Π_n we refer to a program with n variables $\{x_1, \dots, x_n\}$, i.e., $var(\Pi_n) = \{x_1, \dots, x_n\}$. The size $|\Pi_n|$ of a program Π_n , is the number of rules in it.

2.2 Problem Representation and Succinctness

A *string* is a finite sequence of *bits* from $\{0, 1\}$. A string w of length n (i.e., $w \in \{0, 1\}^n$) can be written as $w_1 w_2 \dots w_n$, in which each bit $w_i \in \{0, 1\}$. Note that a string $w \in \{0, 1\}^n$ defines a subset of variables $\{x_1, \dots, x_n\}$, e.g., 1010 stands for $\{x_1, x_3\}$. So a set of variables and a string is regarded as the same. A *problem* (or *language*) L is a set of strings.

Definition 2.1 (Problem Representation). *A problem L can be represented in a class of programs $\mathcal{C}$ (i.e., $L \in \mathcal{C}$), if there exists a sequence of programs $\{\Pi_n\}$ ($n = 1, 2, \dots$) in $\mathcal{C}$ that computes L , i.e., for every string $w \in \{0, 1\}^n$,*

$$w \in L \Leftrightarrow w \in Ans(\Pi_n).$$

Moreover, say L has polynomial representations in $\mathcal{C}$ (i.e., $L \in \text{Poly-}\mathcal{C}$), if $L \in \mathcal{C}$ and $|\Pi_n|$ is bounded by a polynomial $p(n)$.

The following concept is adopted from [17, 13].

Definition 2.2 (Succinctness). Let $\mathcal{C}, \mathcal{C}'$ be two classes of programs and for every problem L , $L \in \mathcal{C} \Leftrightarrow L \in \mathcal{C}'$. Say $\mathcal{C}$ is at least as succinct as $\mathcal{C}'$ (i.e., $\mathcal{C}' \preceq \mathcal{C}$), if for every problem L ,

$$L \in \text{Poly-}\mathcal{C}' \Rightarrow L \in \text{Poly-}\mathcal{C}.$$

If $L \in \text{Poly-}\mathcal{C}$ but $L \notin \text{Poly-}\mathcal{C}'$ (i.e., $\mathcal{C} \not\preceq \mathcal{C}'$), then L separates $\mathcal{C}$ from $\mathcal{C}'$. If $\mathcal{C}' \preceq \mathcal{C}$ and $\mathcal{C} \not\preceq \mathcal{C}'$, then $\mathcal{C}$ is strictly more succinct than $\mathcal{C}'$ (i.e., $\mathcal{C}' \prec \mathcal{C}$). Moreover, $\mathcal{C}, \mathcal{C}'$ are succinctly incomparable if there is a problem L separates $\mathcal{C}$ from $\mathcal{C}'$, and vice versa (i.e., $\mathcal{C} \not\preceq \mathcal{C}'$ and $\mathcal{C}' \not\preceq \mathcal{C}$).

Please note that the above notions also apply to formalisms like PF or boolean circuits, etc.

2.3 The PARITY Problem

The PARITY problem is defined as:

$$\text{PARITY} = \{\text{Binary strings with an odd number of 1's}\}.$$

We may simply call a string in PARITY an odd string, and PARITY_n denotes the set of odd strings of length n . Observe that PARITY_n contains 2^{n-1} strings. It is not hard to see that PARITY_n for $n = 1, 2$ can be computed by normal programs $\Pi_1 = \{x_1 \leftarrow \}$ and $\Pi_2 = \{x_1 \leftarrow \text{not } x_2, x_2 \leftarrow \text{not } x_1\}$ respectively. Since $\text{Ans}(\Pi_1) = \{1\}$ (i.e., $\{x_1\}$), and $\text{Ans}(\Pi_2) = \{10, 01\}$ (i.e., $\{x_1\}, \{x_2\}$). However, as stated below, PARITY_n for $n \geq 3$ have no representations in normal programs.

Theorem 2.1 ($\text{PARITY} \notin \text{LP}$). *PARITY cannot be represented by normal programs.*

Proof. Suppose there is a normal program Π_n that computes PARITY_n for a fixed $n \geq 3$. Then $\{x_1\}$ and $\{x_1, x_2, x_3\}$, which are two odd strings, belong to $\text{Ans}(\Pi_n)$. However, this is impossible since it contradicts the *anti-chain* property of Π_n [28]: if strings $I, I' \in \text{Ans}(\Pi_n)$ and $I \subseteq I'$ then $I = I'$. $\square$

On the other hand, the anti-chain property is suppressed in CP. E.g., the answer set 111 of program (2) is a superset of the other three answer sets 100, 010, 001. Clearly, program (2) represents PARITY_3 , moreover, it suggests a “pattern” for representing PARITY_n : The first part of the program (e.g., the first two rules in (2)) generates all possible strings of $n - 1$ bits, the second part identifies the last bit to produce an odd string.

Therefore, it is straightforward to give a sequence of canonical programs $\{\Pi_n\}$ for PARITY_n . The following is a PARITY_4 program generated from the pattern:

$$\begin{array}{ll} x_1 \leftarrow \text{not not } x_1, & x_4 \leftarrow x_1, x_2, \text{not } x_3, \\ x_2 \leftarrow \text{not not } x_2, & x_4 \leftarrow x_1, x_3, \text{not } x_2, \\ x_3 \leftarrow \text{not not } x_3, & x_4 \leftarrow x_2, x_3, \text{not } x_1, \\ & x_4 \leftarrow \text{not } x_1, \text{not } x_2, \text{not } x_3. \end{array} \quad (4)$$

Please note that the number of rules involved in the second part of the pattern grows exponentially, since the number of odd strings with the last bit 1 grows exponentially.

Theorem 2.2 ($\text{PARITY} \in \text{CP}$). *PARITY can be represented by exponential size canonical programs.*

By PF we denote propositional formulas built on classical connectives $\{\wedge, \vee, \neg\}$ with boolean variables. Related concepts like *satisfaction*, *model* etc., are defined as usual. By $M(\phi)$ we denoted the set of models of ϕ . The *size* $|\phi|$ of a formula ϕ is the number of connectives occur in it. PARITY_n for $n = 1, 2$ can be represented by formulas x_1 and $(x_1 \wedge \neg x_2) \vee (\neg x_2 \wedge x_1)$. Furthermore, it is a textbook result that PARITY_n for $n \geq 3$ has polynomial size formulas in PF, i.e., $\text{PARITY} \in \text{NC}^1/\text{poly}$ (or Poly-PF) [3, 21].

3 Boolean Circuits, Completion and PARITY_n Programs for $n \leq 2$

3.1 Boolean Circuits

A (*boolean*) *circuit* is a directed, cycle-free graph where each node is either a *gate* marked with one of $\{\wedge, \vee, \neg\}$ or a boolean variable. The *in-degree* (resp. *out-degree*) of a node is called its *fan-in* (resp. *fan-out*). A node marked with a variable always has fan-in 0 and is called an *input*. The *output* of the circuit is one gate designated with fan-out 0.

The *value* of a circuit C_n under inputs $x_1, \dots, x_n$, denoted by $C_n(x_1, \dots, x_n)$, is the value of the output obtained from an iterative calculation through the inputs and the intermediate gates in the usual way. The *size* $|C_n|$ of a circuit C_n is the number of gates occur in it. The *depth* of a circuit is the length of the longest path from an input to the output. We say a circuit *computes* (or *represents*) a problem $L \subseteq \{0, 1\}^n$, if $w \in L \Leftrightarrow C_n(w) = 1$. E.g., a circuit C_2 that computes PARITY_2 is shown in Fig. 1. If L consists of strings of arbitrary lengths, then we introduce a sequence of circuits $\{C_n\}(n = 1, 2, \dots)$ to represent L , as indicated in Definition 2.1.

A circuit is said with *bounded fan-in* if each gate has at most fan-in 2. If we do not have such restriction then the circuit is with *unbounded fan-in*. The class AC^0




Figure 1: A Parity₂ Circuit

exactly contains all problems that can be computed by a sequence of circuits $\{C_n\}$ in which the circuits C_n have *constant* depth and polynomial size $p(n)$.

E.g., a sequence of polynomial size CNFs $\{\psi_n\}$ computes an AC^0 language, in which a CNF is a *conjunction* of *clause* of the form $(L_1 \vee \dots \vee L_m)$, where each L_i is either a variable x or a negated variable $\neg x$. Observe that CNF has constant depth 2 ($\neg$ is usually not counted in the depth), and each clause can be regarded as an unbounded fan-in gate $\vee$ with m inputs. Note that $\{\psi_n\}$ cannot represent PARITY since $PARITY \notin AC^0$. For more details about circuits, please see [3].

3.2 Completion and Related Theorems

The *completion* $Comp(\Pi)$ [6, 10] of a canonical program Π , consists of a set (or conjunction) of formulas⁴:

- $x \equiv \tilde{B}_1 \vee \tilde{B}_2 \vee \dots \vee \tilde{B}_m$, where $x \leftarrow B_1, \dots, x \leftarrow B_m$ are all rules in Π with head x , and each $\tilde{B}_i$ is the conjunction of rule elements in B_i with connective *not* replaced by $\neg$,
- $x \equiv \perp$, if x is not a head of any rule in Π ,
- $\neg \tilde{B}$, if a rule $\perp \leftarrow B$ is in Π .

Proposition 3.1. *Let Π be an arbitrary canonical program. Then $Comp(\Pi)$ is a constant depth, unbounded fan-in circuit whose size is polynomially bounded by $|\Pi|$.*

Proof. All propositional formulas are circuits of fan-out 1, so $Comp(\Pi)$ is definitely a circuit. Clearly, its size is polynomially bounded by $|\Pi|$, and its depth is a constant for arbitrary program Π . Moreover, there are no restrictions on the number of rule elements in a body or the number of rules in Π , therefore the corresponding gates in $Comp(\Pi)$ are with unbounded fan-in. $\square$

It is well-known that every answer set of a canonical program Π is a *model* of $Comp(\Pi)$, but the inverse is generally not hold. E.g., the completion of the program $x \leftarrow x$ has two models $\{x\}$ and $\emptyset$, while it has a unique answer set $\emptyset$. It turns

⁴For convenience, we slightly abuse the connective $\equiv$ here.

out that $x \leftarrow x$ gives rise to a so-called *loop*, which leads to an inappropriate model. It is shown in [29, 23] that the so-called *loop formulas* $LF(\Pi)$ nicely eliminate inappropriate models of $Comp(\Pi)$, s.t. the models of the union (or conjunction) of $LF(\Pi)$ and $Comp(\Pi)$ are coincided with $Ans(\Pi)$.

The (positive) *dependency graph* [2] of a canonical program Π is a pair (N, E) in which the set of nodes $N = var(\Pi)$, and E contains a directed edge (x, x') iff there is a rule $H \leftarrow B$ in Π s.t. $H = x$ and $x' \in B$. Note that rule elements of the form *not* x' or *not not* x' in B do not contribute to the edges. A *non-empty* set of variables $U \subseteq var(\Pi)$ is called a *loop* of Π , if i) U is a *singleton* $\{x\}$ and $(x, x) \in E$, or ii) U is not a singleton and the restriction of the graph on U is *strongly connected*.

Let U be a loop of Π , define $R^-(U, \Pi) = \{H \leftarrow B \in \Pi : H \in U, \neg \exists \text{ variable } x \in B \text{ s.t. } x \in U\}$. Let $\{B_1, \dots, B_m\}$ be all the bodies of the rules in $R^-(U, \Pi)$, then the *loop formula* $LF(U, \Pi)$ is the following:

$$\neg[\tilde{B}_1 \vee \dots \vee \tilde{B}_m] \supset \bigwedge_{x \in U} \neg x. \quad (5)$$

$LF(\Pi)$ denotes the conjunction of all loop formulas of Π .

Theorem 3.1 (Lin-Zhao Theorem[29, 23]). *Let Π be a canonical program. Then Π is equivalent to $Comp(\Pi) \cup LF(\Pi)$, i.e., $Ans(\Pi) = M(Comp(\Pi) \cup LF(\Pi))$.*

By Theorem 3.1 (or the (generalized) Fages theorem [11, 10, 33]), if Π has no loops, then $LF(\Pi)$ is a tautology $\top$ and Π is equivalent to $Comp(\Pi)$ (i.e., *completion-equivalent*).

3.3 PARITY_n Programs for $n \leq 2$

Proposition 3.2. *Let Π_1 be a PARITY₁ canonical program. Then Π_1 is equivalent to $Comp(\Pi_1)$.*

Proof. By Theorem 3.1, the unique answer set $\{x_1\}$ of Π_1 is a model of $Comp(\Pi_1) \cup LF(\Pi_1)$, which also is a model of $LF(\Pi_1)$. There are two cases about the loops in Π_1 : (i) Π_1 has no loops. $LF(\Pi_1)$ is simply $\top$; (ii) Π_1 has a singleton loop $\{x_1\}$. Recall that $LF(\Pi_1)$ is a formula of the form $\neg[\tilde{B}_1 \vee \dots \vee \tilde{B}_m] \supset \neg x_1$, in which $B_1 \dots B_m$ are all the bodies of rules in $R^-(\{x_1\}, \Pi_1)$. In both cases, $\emptyset$ is a model of $LF(\Pi_1)$, so $LF(\Pi_1)$ is a tautology. Therefore, Π_1 is equivalent to $Comp(\Pi_1)$. $\square$

Observe that Proposition 3.2 does not hold for PARITY₂ programs. Consider the following PARITY₂ program:

$$\begin{aligned} x_1 &\leftarrow \text{not } x_2, & x_1 &\leftarrow x_1, \\ x_2 &\leftarrow \text{not } x_1, & x_2 &\leftarrow x_2. \end{aligned} \quad (6)$$

Clearly, $\{x_1, x_2\}$ (i.e., 11) is not an answer set of (6), but a model of its completion $\{x_1 \equiv x_1 \vee \neg x_2, x_2 \equiv x_2 \vee \neg x_1\}$.

Note that the rules $\{x_1 \leftarrow x_1, x_2 \leftarrow x_2\}$ contribute to so-called *singleton loops*. We may check that without the above two rules, program (6) is a completion-equivalent PARITY_2 program. In fact, such “singleton loop” rules can be always safely removed, as stated in Proposition 3.3.

Let Π be a basic program and I be a set of variables, define the Knaster-Tarski operator [2] as $T_\Pi(I) = \{H : H \leftarrow B \in \Pi \text{ and } I \models B\}$. The operator T is monotone w.r.t. I therefore has a *least fixed point* $T_\Pi^\infty(\emptyset)$, which can be computed by: (i) $T_\Pi^0(\emptyset) = \emptyset$; (ii) $T_\Pi^{i+1}(\emptyset) = T_\Pi(T_\Pi^i(\emptyset))$ and (iii) $T_\Pi^\infty(\emptyset) = \bigcup_{i \geq 0} (T_\Pi^i(\emptyset))$. Moreover, T is also monotone w.r.t. Π for a given I , i.e., $T_\Pi(I) \subseteq T_{\Pi'}(I)$ if $\Pi \subseteq \Pi'$. It is pointed out in [15, 33] that $I \in \text{Ans}(\Pi)$ iff $I = T_{\Pi'}^\infty(\emptyset)$ for a canonical program Π .

Proposition 3.3. *Let Π be a canonical program. Then removing each rule $x \leftarrow B \in \Pi$ with $x \in \text{var}(B)$ results in a program Π' s.t. $\text{Ans}(\Pi) = \text{Ans}(\Pi')$.*

Proof. It is sufficient to show $T_{\Pi'}^\infty(\emptyset) = T_\Pi^\infty(\emptyset)$ for any set I of variables. Suppose $H \in T_{\Pi'}^\infty(\emptyset)$ for some I , then $\exists i > 0$, $H \in T_{\Pi'}^i(\emptyset)$ and $H \notin T_{\Pi'}^{i-1}(\emptyset)$. It is not hard to see that H must be obtained from a rule $H \leftarrow B$ in Π s.t. $H \notin \text{var}(B)$, $H \leftarrow \text{var}(B) \in \Pi'$ and $T_{\Pi'}^{i-1}(\emptyset) \models \text{var}(B)$. Note that $H \leftarrow B \in \Pi'$ and $H \leftarrow \text{var}(B)$ is in Π' as well. Now we show $H \in T_\Pi^\infty(\emptyset)$. Suppose $H \in T_{\Pi'}^1(\emptyset)$. So a rule $H \leftarrow$ is in Π' and Π' , clearly $H \in T_{\Pi'}^\infty(\emptyset)$. Let $k > 1$ and assume for all $i < k$, $T_{\Pi'}^i(\emptyset) \subseteq T_\Pi^\infty(\emptyset)$. Suppose $H' \in T_{\Pi'}^k(\emptyset)$, then $\exists H' \leftarrow \text{var}(B') \in \Pi'$ s.t. $T_{\Pi'}^{k-1}(\emptyset) \models \text{var}(B')$. Obviously $H' \in T_\Pi^\infty(\emptyset)$ since $H' \leftarrow \text{var}(B') \in \Pi'$ and $T_{\Pi'}^\infty(\emptyset) \models \text{var}(B')$ by induction hypothesis. Therefore $T_{\Pi'}^\infty(\emptyset) \subseteq T_\Pi^\infty(\emptyset)$. Note that $\Pi' \subseteq \Pi$ since $\Pi' \subseteq \Pi$. It follows that $T_{\Pi'}^\infty(\emptyset) \subseteq T_\Pi^\infty(\emptyset)$ due to the monotonicity of operator T . Hence $T_{\Pi'}^\infty(\emptyset) = T_\Pi^\infty(\emptyset)$. $\square$

It turns out that we have a more general observation: deleting *all* rules with variables in the body (thus removing all loops) does not affect the answer sets of a PARITY_2 program!

Proposition 3.4. *Let Π_2 be a PARITY_2 canonical program. Then there is a PARITY_2 program Π'_2 which is equivalent to $\text{Comp}(\Pi'_2)$ and $|\Pi'_2| \leq |\Pi_2|$.*

Proof. W.l.o.g., assume Π_2 has no singleton loops. Let $\Pi'_2 = \{H \leftarrow B \in \Pi_2 : \text{var}(B) = \emptyset\}$, clearly $\Pi'_2 \subseteq \Pi_2$ and thus $|\Pi'_2| \leq |\Pi_2|$. To see Π'_2 is also a PARITY_2 program, it is sufficient to show for any $I \in \text{Ans}(\Pi_2)$, $Cn(\Pi_2) = Cn(\Pi'_2)$. Suppose $H \in I$, i.e., $H \in Cn(\Pi_2)$. We claim that H must be obtained from a rule $H \leftarrow B$ in Π_2 s.t. (i) $I \models B$, and (ii) $\text{var}(B) = \emptyset$. Clearly (i) holds. To see (ii), note that Π_2 has exactly two answer sets $\{x_1\}$ and $\{x_2\}$. W.l.o.g., let $I = \{x_1\}$ thus $H = x_1$. Since Π_2 has no singleton loops, $x_1 \notin \text{var}(B)$, and $x_2 \notin \text{var}(B)$ since $I \models B$. Hence $\text{var}(B) = \emptyset$.

Now it is easy to see $H \leftarrow B \in \Pi'_2$ and $H \leftarrow \in \Pi'_2$ since $I \models B$ and $\text{var}(B) = \emptyset$. Thus $H \in Cn(\Pi'_2)$. Therefore $Cn(\Pi_2) \subseteq Cn(\Pi'_2)$. Since $\Pi'_2 \subseteq \Pi_2$

Π_2 , we have $Cn(\Pi_2^I) \subseteq Cn(\Pi_2^I)$ due to the monotonicity of operator $Cn(\cdot)$. Consequently, $Cn(\Pi_2^I) = Cn(\Pi_2^I)$. Observe that Π_2' has no loops, so Π_2' is equivalent to $Comp(\Pi_2')$. $\square$

Consider the following PARITY₂ program (7), which has a non-singleton loop $\{x_1, x_2\}$ but not completion-equivalent. One may see that removing the two rules in the second line makes it completion-equivalent, without affecting its answer sets.

$$\begin{aligned} x_1 &\leftarrow \text{not } x_2, & x_2 &\leftarrow \text{not } x_1, \\ x_1 &\leftarrow x_2, \text{not not } x_1, & x_2 &\leftarrow x_1, \text{not not } x_2. \end{aligned} \quad (7)$$

In the following, we shall introduce a general approach to simply an arbitrary PARITY program to be completion-equivalent.

4 General Simplification of PARITY_n Programs

Let B be a set of rule elements built on associated variables $V = \{x_1, \dots, x_n\}$. We say B is *consistent* if there is a set of variables I s.t. $I \models B$. Define $S(B)$ to be the set $\{I \subseteq V : I \models B\}$. E.g., let $V = \{x_1, x_2, x_3, x_4\}$ and $B = \{x_2, \text{not } x_3, \text{not not } x_4\}$, then B is consistent and $S(B) = \{\{x_1, x_2, x_4\}, \{x_2, x_4\}\} = \{1101, 0101\}$. Clearly, if B is not consistent then $S(B) = \emptyset$. Note that if a rule has an inconsistent body, then it is redundant and can be safely removed.

We say B *covers* a variable $x \in V$ iff $x \in B$ or $\text{not } x \in B$ or $\text{not not } x \in B$. If B covers every variable in V then B *fully covers* V . E.g., $B = \{x_1, \text{not } x_2, \text{not not } x_3\}$ fully covers $V = \{x_1, x_2, x_3\}$. Obviously, B is consistent and fully covers V iff $S(B)$ contains a unique string.

In the next section, we stipulate that the set of associated variables is $\text{var}(\Pi_n)$ whenever Π_n is the program under discussion, we also assume that a PARITY program has no singleton-loops and contains no inconsistent bodies.

4.1 Simplifying Full Coverage Rules

A rule $H \leftarrow B \in \Pi_n$ is a *full coverage rule* if B fully covers $\text{var}(\Pi_n)$.

Lemma 4.1. *Let Π_n be a PARITY_n program. Suppose there is a rule $x \leftarrow B$ in Π_n s.t. $\text{not not } x \in B$ and $S(B)$ contains a unique even string. Then removing $x \leftarrow B$ from Π_n results in a PARITY_n program Π_n' .*

Proof. We show for any set I of variables, $I = Cn(\Pi_n^I)$ iff $I = Cn(\Pi_n'^I)$. Observe that $\Pi_n' \subseteq \Pi_n$, then $Cn(\Pi_n'^I) \subseteq Cn(\Pi_n^I)$ for any I . So it is sufficient to show $Cn(\Pi_n^I) \subseteq Cn(\Pi_n'^I)$. Assume $Cn(\Pi_n^I) \not\subseteq Cn(\Pi_n'^I)$ for some I . It must be the case that $x \in Cn(\Pi_n^I)$ and $x \notin Cn(\Pi_n'^I)$ since $\Pi_n' \cup \{x \leftarrow B\} = \Pi_n$. Moreover, we have $x \leftarrow \text{var}(B) \in \Pi_n^I$ and $Cn(\Pi_n^I) \models \text{var}(B)$. The former implies that $I \models B \setminus \text{var}(B)$. Since $\text{not not } x \in B \setminus \text{var}(B)$, we have $I \models \text{not not } x$ (i.e., $x \in I$).

Now suppose $I = Cn(\Pi_n^I)$, then I is an odd string. However, recall that $I \models B \setminus \text{var}(B)$ and $I = Cn(\Pi_n^I) \models \text{var}(B)$. Hence we have $I \models B$, i.e., $I \in S(B)$. This contradicts the fact that $I \in S(B)$ is an even string. So $Cn(\Pi_n^I) \subseteq Cn(\Pi_n^{II})$.

Suppose $I = Cn(\Pi_n^{II})$. As mentioned above, $Cn(\Pi_n^I) \not\subseteq Cn(\Pi_n^{II})$ implies that $x \notin Cn(\Pi_n^{II})$ and $x \in I$. However, recall that $I = Cn(\Pi_n^{II})$, hence $x \in Cn(\Pi_n^{II})$, a contradiction. So $Cn(\Pi_n^I) \subseteq Cn(\Pi_n^{II})$. $\square$

Note that Lemma 4.1 also justifies our simplification for (7).

Lemma 4.2. *Let Π_n be a PARITY_n program. Suppose there is a rule $x \leftarrow B$ in Π_n s.t. not $x \in B$ and $S(B)$ contains a unique odd string. Then replacing its body B with $B' = B \setminus \{\text{not not } x\}$ results in a PARITY_n program Π'_n .*

Proof. We show that $I = Cn(\Pi_n^I)$ iff $I = Cn(\Pi_n^{II})$ for any set I of variables. Suppose $I = Cn(\Pi_n^I)$, we shall prove $Cn(\Pi_n^I) = Cn(\Pi_n^{II})$. Consider the following cases:

- $I \models B \setminus \text{var}(B)$. Since $B' = B \setminus \{\text{not not } x\}$, clearly, $B' \setminus \text{var}(B') \subseteq B \setminus \text{var}(B)$, hence $I \models B' \setminus \text{var}(B')$. It follows that $x \leftarrow \text{var}(B) \in \Pi_n^I$ and $x \leftarrow \text{var}(B') \in \Pi_n^{II}$. Furthermore, note that $\Pi_n \setminus \{x \leftarrow B\} = \Pi'_n \setminus \{x \leftarrow B'\}$ and $\text{var}(B) = \text{var}(B')$, thus $\Pi_n^I = \Pi_n^{II}$. So $Cn(\Pi_n^I) = Cn(\Pi_n^{II})$.
- $I \not\models B \setminus \text{var}(B)$. Consider the following subcases:
 - $I \not\models B' \setminus \text{var}(B')$. Similarly, we have $\Pi_n^{II} = \Pi_n^I$, thus $Cn(\Pi_n^{II}) = Cn(\Pi_n^I)$.
 - $I \models B' \setminus \text{var}(B')$. Clearly, in this case $I \not\models \text{not not } x$. Now suppose $I \models \text{var}(B')$, so we have $I \models B'$. Recall that (i) $\text{not not } x \in B$, (ii) $x \notin B$ since Π_n has no singleton loops, (iii) $B' = B \setminus \{\text{not not } x\}$ and (iv) $S(B)$ contains a unique odd string, say I' . It follows that $S(B') = \{I', I' \setminus \{x\}\}$. Obviously I must be $I' \setminus \{x\}$ since $I' \models \text{not not } x$. However, this is a contradiction since $I' \setminus \{x\}$ is an even string and I is an odd string since I is an answer set of Π_n . So suppose $I \not\models \text{var}(B)$. Note that in this case $\Pi_n^{II} = \Pi_n^I \cup \{x \leftarrow \text{var}(B)\}$, we show $Cn(\Pi_n^I) = Cn(\Pi_n^I \cup \{x \leftarrow \text{var}(B)\})$, i.e., $Cn(\Pi_n^I) = Cn(\Pi_n^{II})$. Firstly, $Cn(\Pi_n^I) \subseteq Cn(\Pi_n^I \cup \{x \leftarrow \text{var}(B)\})$ due to the monotonicity of operator $Cn(\cdot)$. Assume $Cn(\Pi_n^I \cup \{x \leftarrow \text{var}(B)\}) \not\subseteq Cn(\Pi_n^I)$, it must be $Cn(\Pi_n^I) \models \text{var}(B)$ and $x \in Cn(\Pi_n^I \cup \{x \leftarrow \text{var}(B)\})$, $x \notin Cn(\Pi_n^I)$. However this is impossible since $I = Cn(\Pi_n^I)$ and $I \not\models \text{var}(B)$. Therefore $Cn(\Pi_n^I \cup \{x \leftarrow \text{var}(B)\}) \subseteq Cn(\Pi_n^I)$.

Suppose $I = Cn(\Pi_n^{II})$, we shall prove $Cn(\Pi_n^I) = Cn(\Pi_n^{II})$. Consider the following cases:

- $x \leftarrow \text{var}(B') \notin \Pi_n^{II}$. Clearly, $I \not\models B' \setminus \text{var}(B')$. So $I \not\models B \setminus \text{var}(B)$ since $B' \setminus \text{var}(B') \subseteq B \setminus \text{var}(B)$. Therefore $x \leftarrow \text{var}(B) \notin \Pi_n^I$ and we have $\Pi_n^{II} = \Pi_n^I$. Hence $Cn(\Pi_n^{II}) = Cn(\Pi_n^I)$.

- $x \leftarrow \text{var}(B') \in \Pi_n^I$. There are two subcases:
 - $x \leftarrow \text{var}(B) \in \Pi_n^I$. Similarly, $\Pi_n^I = \Pi_n^I$ and then $Cn(\Pi_n^I) = Cn(\Pi_n^I)$.
 - $x \leftarrow \text{var}(B) \notin \Pi_n^I$. Clearly, $I \not\models \text{not not } x$, i.e., $x \notin I$. Furthermore, recall that $\Pi_n^I = \Pi_n^I \cup \{x \leftarrow \text{var}(B')\}$. We shall show $Cn(\Pi_n^I) = Cn(\Pi_n^I)$. Obviously $Cn(\Pi_n^I) \subseteq Cn(\Pi_n^I)$. Now assume $Cn(\Pi_n^I) \not\subseteq Cn(\Pi_n^I)$. It must be the case that $x \in Cn(\Pi_n^I)$ but $x \notin Cn(\Pi_n^I)$. However, since $I = Cn(\Pi_n^I)$, we have $x \in I$, a contradiction. So $Cn(\Pi_n^I) \subseteq Cn(\Pi_n^I)$, therefore $Cn(\Pi_n^I) = Cn(\Pi_n^I)$.

□

4.2 Standard PARITY_n Programs

A PARITY_n program Π_n is *standard* if for each rule $x \leftarrow B \in \Pi_n$, *not not* $x \notin B$ whenever $S(B \cup \{x\})$ contains a unique string. E.g., the PARITY program (2) is standard, while (7) is not. Note that if Π_n is standard, then for any rule $x \leftarrow B \in \Pi_n$, B does not cover x , i.e., $x \notin B$, *not* $x \notin B$ and *not not* $x \notin B$, since Π_n has no singleton loops and $S(B \cup \{x\})$ is consistent.

Proposition 4.1. *Let Π_n be a PARITY_n program. Then there is a standard PARITY_n program Π'_n s.t. $|\Pi'_n| \leq |\Pi_n|$.*

Proof. For each rule $x \leftarrow B \in \Pi_n$ in which *not not* $x \in B$ and $S(B)$ contains a unique string: (i) Delete $x \leftarrow B$ from Π_n if $S(B)$ contains an even string; (ii) Remove *not not* x from B if $S(B)$ contains an odd string. By Lemma 4.1 and 4.2, the above procedure results in a standard PARITY_n program Π'_n and $|\Pi'_n| \leq |\Pi_n|$. □

Proposition 4.2. *Let Π_n be a standard PARITY_n program. Then Π_n is equivalent to its completion $\text{Comp}(\Pi_n)$.*

The proof idea of Proposition 4.2 is that every standard PARITY_n program Π_n can be equivalently rewritten to a loop-free program Π'_n by replacing each $x \in \text{var}(B)$ with *not not* x for every rule body B in Π_n . By the Lin-Zhao Theorem or the (generalized) *Fages Theorem*, Π'_n is equivalent to its completion $\text{Comp}(\Pi'_n)$. And then the proposition follows from the fact that $\text{Comp}(\Pi'_n) = \text{Comp}(\Pi_n)$, since *not* is treated as classical negation $\neg$ in the completion. The detailed proof is presented in subsection 4.3.

4.3 Proof of Proposition 4.2

For technical reasons, we divide the rewriting procedure into two steps, in the first step a standard PARITY program is converted to so-called *almost pure* program and in the second step the program is converted to a *pure* one, i.e., a PARITY program that does not have any loops. Before doing so we show some lemmas.

Lemma 4.3. *Let Π_n be a standard PARITY_n program. For each rule $x \leftarrow B \in \Pi_n$, if $S(B \cup \{x\})$ contains a unique string, then the string must be odd.*

Proof. Since Π_n is standard, B does not cover x . So we have $S(B) = \{I, I \setminus \{x\}\}$. Assume I is an even string, then $I \setminus \{x\}$ must be an odd string. It follows that $I \setminus \{x\}$ is not closed under $x \leftarrow B$, since $I \setminus \{x\} \models B$ but $I \setminus \{x\} \not\models x$. However, Π_n is a PARITY_n program, every odd string must be closed under $x \leftarrow B$. A contradiction. $\square$

Lemma 4.4. *Let Π_n be a PARITY_n program.*

- (i) *If there is a rule $x \leftarrow B \in \Pi_n$ s.t. B is consistent and $B \cup \{x\}$ does not fully cover $\text{var}(\Pi_n)$, then $\text{not not } x \in B$.*
- (ii) *If there is a rule $H \leftarrow B \in \Pi_n$ s.t. B is consistent and $B \cup \{H\}$ is inconsistent, then B fully covers $\text{var}(\Pi_n)$.*

Proof. Note that for any rule $x \leftarrow B$ in a PARITY_1 program, $B \cup \{x\}$ must fully cover $\text{var}(\Pi_1)$ since Π_1 involves only one variable. So in the following we consider $n \geq 2$.

(i) Equivalently, we show that if B is consistent and $\text{not not } x \notin B$, then $B \cup \{x\}$ fully covers $\text{var}(\Pi_n)$. Assume $B \cup \{x\}$ does not fully cover $\text{var}(\Pi_n)$. It follows that B covers $0 \leq i < n$ variables in $\text{var}(\Pi_n)$ (i.e., B does not fully cover $\text{var}(\Pi_n)$). Consider the following cases:

- *not $x \in B$.* Note that B is consistent and $n \geq 2$. It is not hard to see $S(B)$ has exactly $2^{n-i-1} \geq 1$ odd strings. It means there is at least one odd string I , $I \models B$ and $I \not\models x$. Therefore I is not close under $x \leftarrow B$. However, since Π_n is a PARITY_n program, every odd string must be closed under $x \leftarrow B$. A contradiction.
- *not $x \notin B$.* B does not cover x , since $\text{not not } x \notin B$ and $x \notin B$ for Π_n has no singleton loops. Recall that B is consistent and $n \geq 2$, thus $S(B)$ has exactly 2^{n-i-1} odd strings. Obviously, half of these strings do not satisfy x . To be more precise, there are 2^{n-i-2} odd strings I , $I \models B$ and $I \not\models x$. We have $2^{n-i-2} \geq 1$ since i is at most $n-2$. In other words, there is at least one odd string I which is not close under $x \leftarrow B$. Again a contradiction.

Consequently, $B \cup \{x\}$ must fully cover $\text{var}(\Pi_n)$.

(ii) There are two cases about H :

- *H is $\perp$.* Assume B does not fully cover $\text{var}(\Pi_n)$, i.e., B covers i variables in $\text{var}(\Pi_n)$ with $0 \leq i < n$. Since B is consistent, it is easy to see $S(B)$ has exactly $2^{n-i-1} \geq 1$ odd strings. So there exists at least one odd string I is not closed under $\perp \leftarrow B$. A contradiction.
- *H is a variable $x \in \text{var}(\Pi_n)$.* Since $B \cup \{x\}$ is inconsistent, we have $\text{not } x \in B$. It is not hard to see in this case $x \leftarrow B$ can be rewritten as $\perp \leftarrow B$. By an argument similar to the above, B must fully cover $\text{var}(\Pi_n)$.

□

4.3.1 Almost Pure PARITY_n Programs

Let Π_n be a standard PARITY_n program in CP, by $F^-(\Pi_n)$ we denote the set of rules $H \leftarrow B \in \Pi_n$ s.t. $B \cup \{H\}$ does not fully cover $\text{var}(\Pi_n)$, by $F^+(\Pi_n)$ we denote $\Pi_n \setminus F^-(\Pi_n)$. If for each rule $H \leftarrow B \in F^+(\Pi_n)$ we have $\text{var}(B) = \emptyset$, then Π_n is called *almost pure*.

By Lemma 4.4, it is not hard to see that every rule of the form $x \leftarrow B, \text{not not } x$ is in $F^-(\Pi_n)$, and every rule of the form $\perp \leftarrow B$ or $x \leftarrow B, \text{not } x$ is in $F^+(\Pi_n)$.

Proposition 4.3. *Let Π_n be a standard PARITY_n program. Then there is an almost pure PARITY_n program Π'_n s.t. $|\Pi'_n| \leq |\Pi_n|$.*

Proof. Let B' be the set obtained from B by replacing every $x \in \text{var}(B)$ with $\text{not not } x$. Note that $I \models B$ iff $I \models B'$ for any set of variables I . Let Π'_n be the program obtained from Π_n by replacing every rule $H \leftarrow B \in F^+(\Pi_n)$ with $H \leftarrow B'$. Clearly Π'_n is almost pure and $|\Pi'_n| \leq |\Pi_n|$. It remains to prove that Π'_n is also a PARITY_n program, i.e., $I = T_{\Pi'_n}^\infty(\emptyset)$ iff $I = T_{\Pi_n}^\infty(\emptyset)$.

($\Rightarrow$) Suppose I is an answer set of Π_n , i.e., $I = T_{\Pi_n}^\infty(\emptyset)$, we shall show $T_{\Pi'_n}^\infty(\emptyset) = T_{\Pi_n}^\infty(\emptyset)$:

- $T_{\Pi'_n}^\infty(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$. Note that $\perp \notin T_{\Pi'_n}^\infty(\emptyset)$ since $T_{\Pi'_n}^\infty(\emptyset)$ is an answer set. Suppose $x \in T_{\Pi'_n}^1(\emptyset)$, then $\exists x \leftarrow B \in \Pi_n$ s.t. $\text{var}(B) = \emptyset$ and $I \models B$. Clearly, we have $x \leftarrow B \in \Pi'_n$. It follows that $x \leftarrow \in \Pi_n^I$ and then $x \in T_{\Pi_n}^\infty(\emptyset)$. Let $k > 1$ and assume for all $i < k$, $T_{\Pi_n}^i(\emptyset) \subseteq T_{\Pi'_n}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n}^k(\emptyset)$ but $x \notin T_{\Pi_n}^{k-1}(\emptyset)$. Then $\exists x \leftarrow B \in \Pi_n$ s.t. $x \leftarrow \text{var}(B) \in \Pi_n^I$ and $T_{\Pi_n}^{k-1}(\emptyset) \models \text{var}(B)$. Observe that either $x \leftarrow B \in \Pi'_n$ or $x \leftarrow B' \in \Pi'_n$. The former implies that $x \leftarrow \text{var}(B) \in \Pi_n^I$, clearly, $T_{\Pi'_n}^\infty(\emptyset) \models \text{var}(B)$ by induction hypothesis, and thus $x \in T_{\Pi'_n}^\infty(\emptyset)$. The latter implies that $x \leftarrow \in \Pi_n^I$, trivially, $x \in T_{\Pi'_n}^\infty(\emptyset)$. Therefore, $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi'_n}^\infty(\emptyset)$.
- $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi'_n}^\infty(\emptyset)$. We first show $\perp \notin T_{\Pi'_n}^\infty(\emptyset)$. Assume $\perp \in T_{\Pi'_n}^\infty(\emptyset)$, then $\exists \perp \leftarrow B_1 \in \Pi'_n$ s.t. $I \models B_1 \setminus \text{var}(B_1)$. Consider its source $\perp \leftarrow B$ in Π_n . Recall that Π_n has no singleton loops and B is consistent since Π_n is standard. Furthermore, $B \cup \{\perp\}$ is inconsistent, then $\perp \leftarrow B \in F^+(\Pi_n)$ by Lemma 4.4 (ii). So $\text{var}(B_1) = \emptyset$, $I \models B_1$ and thus $I \models B$. The latter means that I is not closed under $\perp \leftarrow B \in \Pi_n$, which contradicts the fact that I is an answer set of Π_n . So $\perp \notin T_{\Pi'_n}^\infty(\emptyset)$. Now suppose $x \in T_{\Pi'_n}^1(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi'_n$ s.t. $x \leftarrow \in \Pi_n^I$ and $I \models B_1$. Consider the source of $x \leftarrow B_1$:
 - (i) $x \leftarrow B_1 \in \Pi_n$, $\text{var}(B_1) = \emptyset$. Since $I \models B_1$, $x \leftarrow \in \Pi_n^I$, we have $x \in T_{\Pi_n}^\infty(\emptyset)$.

- (ii) $x \leftarrow B \in F^+(\Pi_n)$, $\text{var}(B) \neq \emptyset$ and $B_1 = B'$. Note that $I \models B$ since $I \models B_1$. Furthermore, I is closed under $x \leftarrow B$ since I is an answer set of Π_n . So $x \in I$, i.e., $x \in T_{\Pi_n}^\infty(\emptyset)$.

Suppose $x \in T_{\Pi_n}^k(\emptyset)$ but $x \notin T_{\Pi_n}^{k-1}(\emptyset)$ for some $k > 1$. It means that $\exists x \leftarrow B_1 \in \Pi_n$ s.t. $\text{var}(B_1) \neq \emptyset$, $x \leftarrow \text{var}(B_1) \in \Pi_n^I$, $I \models B_1 \setminus \text{var}(B_1)$ and $T_{\Pi_n}^{k-1}(\emptyset) \models \text{var}(B_1)$. Note that $\text{var}(B_1) \neq \emptyset$ implies that $x \leftarrow B_1 \in F^-(\Pi_n)$, $B_1 \cup \{x\}$ does not fully cover $\text{var}(\Pi_n)$. By Lemma 4.4 (i), we have *not not* $x \in B_1$. Recall that $I \models B_1 \setminus \text{var}(B_1)$, so $I \models \text{not not } x$, i.e., $x \in T_{\Pi_n}^\infty(\emptyset)$. Therefore, $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$.

($\Leftarrow$) Suppose I is an answer set of Π_n' , i.e., $I = T_{\Pi_n'}^\infty(\emptyset)$, we shall show $T_{\Pi_n'}^\infty(\emptyset) = T_{\Pi_n}^\infty(\emptyset)$:

- $T_{\Pi_n'}^\infty(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$. Note that $\perp \notin T_{\Pi_n'}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n'}^1(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n'$ s.t. $\text{var}(B_1) = \emptyset$, $x \leftarrow \in \Pi_n^I$ and $I \models B_1$. Now consider the source of $x \leftarrow B_1$:
 - (i) $x \leftarrow B_1 \in \Pi_n$. So $x \leftarrow \in \Pi_n^I$ and clearly $x \in T_{\Pi_n}^\infty(\emptyset)$.
 - (ii) $x \leftarrow B \in F^+(\Pi_n)$, $\text{var}(B) \neq \emptyset$ and $B_1 = B$. Note that $I \models B_1 \cup \{x\}$ since $x \in I$ and $I \models B_1$, it follows that $I \models B \cup \{x\}$. Clearly, $B \cup \{x\}$ is consistent and fully covers $\text{var}(\Pi_n)$. By Lemma 4.3, I is exactly the unique odd string in $S(B \cup \{x\})$. Recall that Π_n is a PARITY_n program, so I must be an answer set of Π_n , i.e., $I = T_{\Pi_n}^\infty(\emptyset)$. Therefore $x \in T_{\Pi_n}^\infty(\emptyset)$.

Let $k > 1$ and assume for all $i < k$, $T_{\Pi_n}^i(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n}^k(\emptyset)$ but $x \notin T_{\Pi_n}^{k-1}(\emptyset)$. Then $\exists x \leftarrow B_1 \in \Pi_n$ s.t. $\text{var}(B_1) \neq \emptyset$, $x \leftarrow \text{var}(B_1) \in \Pi_n^I$, $I \models B_1 \setminus \text{var}(B_1)$ and $T_{\Pi_n}^{k-1}(\emptyset) \models \text{var}(B_1)$. Note that $\text{var}(B_1) \neq \emptyset$ implies $x \leftarrow B_1 \in F^-(\Pi_n)$. Moreover, $x \leftarrow \text{var}(B_1) \in \Pi_n^I$. By inductive hypothesis, $T_{\Pi_n}^\infty(\emptyset) \models \text{var}(B_1)$, therefore $x \in T_{\Pi_n}^\infty(\emptyset)$. Consequently, $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$.

- $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi_n'}^\infty(\emptyset)$. We first show $x \in T_{\Pi_n}^\infty(\emptyset)$ implies $x \in T_{\Pi_n'}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n}^1(\emptyset)$, then $\exists x \leftarrow B \in \Pi_n$, $\text{var}(B) = \emptyset$ and $I \models B$. It follows that $x \leftarrow B \in \Pi_n'$ and $x \leftarrow \in \Pi_n^I$. Clearly, $x \in T_{\Pi_n'}^\infty(\emptyset)$. Let $k > 1$ and assume for all $i < k$, $x \in T_{\Pi_n}^i(\emptyset)$ implies $x \in T_{\Pi_n'}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n}^k(\emptyset)$ but $x \notin T_{\Pi_n}^{k-1}(\emptyset)$. Then $\exists x \leftarrow B \in \Pi_n$ s.t. $x \leftarrow \text{var}(B) \in \Pi_n^I$, $\text{var}(B) \neq \emptyset$, $I \models B \setminus \text{var}(B)$ and $T_{\Pi_n}^{k-1}(\emptyset) \models \text{var}(B)$. By induction hypothesis, $T_{\Pi_n}^\infty(\emptyset) \models \text{var}(B)$, i.e., $I \models \text{var}(B)$. Now $I \models B$ since $I \models B \setminus \text{var}(B)$ and $I \models \text{var}(B)$, hence $I \models B'$. Observe that either $x \leftarrow B' \in \Pi_n'$ or

$x \leftarrow B \in \Pi'_n$, in both cases $I \models x$ since I is an answer set of Π'_n and must be closed under every rule of Π'_n . Consequently, $x \in T_{\Pi'_n}^\infty(\emptyset)$ implies $x \in T_{\Pi_n'}^\infty(\emptyset)$. It remains to show $\perp \notin T_{\Pi_n'}^\infty(\emptyset)$. Assume $\perp \in T_{\Pi_n'}^\infty(\emptyset)$, then $\exists \perp \leftarrow B$ in $F^+(\Pi_n)$ s.t. $I \models B \setminus \text{var}(B)$ and $T_{\Pi_n'}^k(\emptyset) \models \text{var}(B)$ for some $k \geq 1$. Notice that the latter means $I \models \text{var}(B)$, since variables $T_{\Pi_n'}^k(\emptyset) \models \text{var}(B)$ implies $T_{\Pi_n'}^\infty(\emptyset) \models \text{var}(B)$ by the previous result and $I = T_{\Pi_n'}^\infty(\emptyset)$. So $I \models B$, i.e., $I \models B'$. However, note that $\perp \leftarrow B'$ in Π'_n and I is not closed under $\perp \leftarrow B'$. This contradicts the fact that I is an answer set of Π'_n . Therefore $\perp \notin T_{\Pi_n'}^\infty(\emptyset)$, and hence $T_{\Pi_n'}^\infty(\emptyset) \subseteq T_{\Pi_n}^\infty(\emptyset)$.

□

4.3.2 Pure PARITY_n Programs

Let Π_n be an almost pure PARITY_n program. If for every rule $H \leftarrow B \in \Pi_n$ we have $\text{var}(B) = \emptyset$, then Π_n is called *pure*. Clearly, a pure program has no loops and is hence completion-equivalent.

Proposition 4.4. *Let Π_n be an almost pure PARITY_n program. Then there is a pure PARITY_n program Π'_n s.t. $|\Pi'_n| \leq |\Pi_n|$.*

Proof. A rule $H \leftarrow B$ is *non-pure* if $\text{var}(B) \neq \emptyset$. We show by induction on the number m of non-pure rules in Π_n . Base step $m = 0$, the claim trivially holds. Let $m > 0$ and assume the claim holds for all almost pure PARITY_n programs containing $j < m$ non-pure rules. Suppose Π_n is an almost pure PARITY_n program with m non-pure rules, and let $H \leftarrow B$ be a non-pure rule in Π_n . Note that $H \leftarrow B$ must be in $F^-(\Pi_n)$ and H is a variable x , since Π_n is almost pure. Let B' be obtained from B by replacing each variable $x \in \text{var}(B)$ with *not not* x . Note that $I \models B$ iff $I \models B'$ for any set of variables I . Let Π be $\Pi_n \setminus \{H \leftarrow B\}$ and let $\Pi''_n = \Pi \cup \{H \leftarrow B'\}$. Clearly, Π''_n is almost pure and $|\Pi''_n| \leq |\Pi_n|$. We shall show that Π''_n is also a PARITY_n program, i.e., $I = T_{\Pi_n}^\infty(\emptyset)$ iff $I = T_{\Pi''_n}^\infty(\emptyset)$.

($\Rightarrow$) Suppose $I = T_{\Pi_n}^\infty(\emptyset)$, we prove $T_{\Pi_n}^\infty(\emptyset) = T_{\Pi''_n}^\infty(\emptyset)$:

- $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi''_n}^\infty(\emptyset)$. Note that $\perp \notin T_{\Pi_n}^\infty(\emptyset)$ since $T_{\Pi_n}^\infty(\emptyset)$ is an answer set. Suppose $x \in T_{\Pi_n}^1(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n$ s.t. $\text{var}(B_1) = \emptyset$ and $I \models B_1$. Clearly, $x \leftarrow B_1 \in \Pi''_n$ and $x \leftarrow \in \Pi''_n$, thus $x \in T_{\Pi''_n}^\infty(\emptyset)$. Let $k > 1$ and assume for all $i < k$, $T_{\Pi_n}^i(\emptyset) \subseteq T_{\Pi''_n}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n}^k(\emptyset)$ but $x \notin T_{\Pi_n}^{k-1}(\emptyset)$. Then $\exists x \leftarrow B_1 \in \Pi_n$ s.t. $\text{var}(B_1) \neq \emptyset$, $x \leftarrow \text{var}(B_1) \in \Pi_n^I$ and $T_{\Pi_n}^{k-1}(\emptyset) \models \text{var}(B_1)$. Hence if $x = H$, $B_1 = B$ then $x \leftarrow B' \in \Pi''_n$, otherwise $x \leftarrow B_1 \in \Pi''_n$. The former implies $x \leftarrow \in \Pi''_n$ since $\text{var}(B') = \emptyset$, and $I \models B'$ due to $I \models B_1$, trivially, $x \in T_{\Pi''_n}^\infty(\emptyset)$. The latter implies $x \leftarrow \text{var}(B_1) \in \Pi''_n$, clearly, $T_{\Pi''_n}^\infty(\emptyset) \models \text{var}(B_1)$ by induction hypothesis, and thus $x \in T_{\Pi''_n}^\infty(\emptyset)$. Therefore, $T_{\Pi_n}^\infty(\emptyset) \subseteq T_{\Pi''_n}^\infty(\emptyset)$.

- $T_{\Pi_n''^I}^\infty(\emptyset) \subseteq T_{\Pi_n''^I}^\infty(\emptyset)$. We first show that $\perp \notin T_{\Pi_n''^I}^\infty(\emptyset)$. Assume $\perp \in T_{\Pi_n''^I}^\infty(\emptyset)$. So $\exists \perp \leftarrow B_1 \in \Pi_n''$ s.t. $\perp \leftarrow \text{var}(B_1) \in \Pi_n''^I$ and $I \models B_1 \setminus \text{var}(B_1)$. Note that $\perp \leftarrow B_1$ must be in $F^+(\Pi_n)$ since Π_n is almost pure. Hence $\text{var}(B_1) = \emptyset$, $I \models B_1$ thus $I \models B$. The latter means that I is not closed under $\perp \leftarrow B_1 \in \Pi_n$, which contradicts the fact that I is an answer set of Π_n . So $\perp \notin T_{\Pi_n''^I}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n''^I}^\infty(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n''$ s.t. $x \leftarrow \in \Pi_n''^I$ and $I \models B_1$. There are two cases about the source of $x \leftarrow B_1$:
 - (i) $x \leftarrow B_1 \in \Pi_n$, $\text{var}(B_1) = \emptyset$. Since $I \models B_1$, so $x \leftarrow \in \Pi_n^I$, $x \in T_{\Pi_n^I}^\infty(\emptyset)$.
 - (ii) $x \leftarrow B_1$ is obtained from $H \leftarrow B \in F^-(\Pi_n)$, i.e., $H = x$, $\text{var}(B) \neq \emptyset$ and $B_1 = B'$. Note that $I \models B$ since $I \models B_1$. Recall that *not not* $x \in B$, so $x \in I$, i.e., $x \in T_{\Pi_n^I}^\infty(\emptyset)$.

Now suppose $x \in T_{\Pi_n''^I}^k(\emptyset)$ but $x \notin T_{\Pi_n''^I}^{k-1}(\emptyset)$ for some $k > 1$. It means that $\exists x \leftarrow B_1 \in \Pi_n''$ s.t. $\text{var}(B_1) \neq \emptyset$, $x \leftarrow \text{var}(B_1) \in \Pi_n''^I$, $I \models B_1 \setminus \text{var}(B_1)$ and $T_{\Pi_n''^I}^{k-1}(\emptyset) \models \text{var}(B_1)$. Since Π_n is almost pure, $\text{var}(B_1) \neq \emptyset$ implies that $x \leftarrow B_1 \in F^-(\Pi_n)$. By Lemma 4.4 (i), *not not* $x \in B_1$. Recall that $I \models B_1 \setminus \text{var}(B_1)$, so $I \models \text{not not } x$, i.e., $x \in T_{\Pi_n^I}^\infty(\emptyset)$. Therefore, $T_{\Pi_n''^I}^\infty(\emptyset) \subseteq T_{\Pi_n^I}^\infty(\emptyset)$.

($\Leftarrow$) Suppose $I = T_{\Pi_n''^I}^\infty(\emptyset)$, we show $T_{\Pi_n''^I}^\infty(\emptyset) = T_{\Pi_n^I}^\infty(\emptyset)$.

- $T_{\Pi_n''^I}^\infty(\emptyset) \subseteq T_{\Pi_n^I}^\infty(\emptyset)$. Note that $\perp \notin T_{\Pi_n''^I}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n''^I}^\infty(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n''$ s.t. $x \leftarrow \in \Pi_n''^I$ and $I \models B_1$. Now consider the source of $x \leftarrow B_1$:
 - (i) $x \leftarrow B_1 \in \Pi_n$ and $\text{var}(B_1) = \emptyset$. It follows that $x \leftarrow \in \Pi_n^I$ and clearly $x \in T_{\Pi_n^I}^\infty(\emptyset)$.
 - (ii) $x \leftarrow B_1$ is obtained from $H \leftarrow B \in F^-(\Pi_n)$, i.e., $H = x$ and $B_1 = B'$. So $x \leftarrow \text{var}(B) \in \Pi_n^I$ and $I \models B$. The latter implies $T_{\Pi_n''^I}^\infty(\emptyset) \models B$ thus $T_{\Pi_n''^I}^\infty(\emptyset) \models \text{var}(B)$. Note that $\Pi_n''^I = \Pi_n^I \cup \{x \leftarrow\}$, and $x \notin \text{var}(B)$ since Π_n is almost pure, it has no singleton loops. We prove by induction that $T_{\Pi_n^I}^\infty(\emptyset) \models \text{var}(B)$. Suppose $x' \in \text{var}(B)$ and $x' \in T_{\Pi_n''^I}^1(\emptyset)$, then $\exists x' \leftarrow B_2 \in \Pi_n''$, $\text{var}(B_2) = \emptyset$ and $I \models B_2$. Clearly, $x' \leftarrow \in \Pi_n^I$, thus $x' \in T_{\Pi_n^I}^\infty(\emptyset)$. Let $s > 1$ and assume for all $t < s$, $x' \in \text{var}(B)$ and $x' \in T_{\Pi_n''^I}^t(\emptyset)$ implies $x' \in T_{\Pi_n^I}^\infty(\emptyset)$. Suppose $x' \in \text{var}(B)$ and $x' \in T_{\Pi_n''^I}^s(\emptyset)$. Then $\exists x' \leftarrow B_2 \in \Pi_n''$, $x' \leftarrow \text{var}(B_2) \in \Pi_n''^I$ and $T_{\Pi_n''^I}^{s-1}(\emptyset) \models \text{var}(B_2)$. Recall that $x \neq x'$ since $x \notin \text{var}(B)$, so $x' \leftarrow \text{var}(B_2) \in \Pi_n^I$. By induction hypothesis, $T_{\Pi_n^I}^\infty(\emptyset) \models \text{var}(B_2)$, $x' \in T_{\Pi_n^I}^\infty(\emptyset)$. Hence $T_{\Pi_n^I}^\infty(\emptyset) \models \text{var}(B)$. Furthermore, $\Pi_n^I = \Pi_n^I \cup \{x \leftarrow \text{var}(B)\}$, so $T_{\Pi_n^I}^\infty(\emptyset) \subseteq T_{\Pi_n''^I}^\infty(\emptyset)$, $T_{\Pi_n^I}^\infty(\emptyset) \models \text{var}(B)$. Therefore $T_{\Pi_n''^I}^\infty(\emptyset) \models x$, i.e., $x \in T_{\Pi_n^I}^\infty(\emptyset)$.

Let $k > 1$ and assume for all $i < k$, $T_{\Pi_n''}^i(\emptyset) \subseteq T_{\Pi_n''}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n''}^k(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n''$, $\text{var}(B_1) \neq \emptyset$, $x \leftarrow \text{var}(B_1) \in \Pi_n''$, $T_{\Pi_n''}^{k-1}(\emptyset) \models \text{var}(B_1)$. Clearly, $x \leftarrow \text{var}(B_1) \in \Pi_n^I$. It follows that $x \leftarrow \text{var}(B_1) \in \Pi_n^I$ since $\Pi_n^I \subseteq \Pi_n''$. By induction hypothesis, $T_{\Pi_n^I}^\infty(\emptyset) \models \text{var}(B_1)$. Hence $T_{\Pi_n^I}^\infty(\emptyset) \models x$, i.e., $x \in T_{\Pi_n^I}^\infty(\emptyset)$. Therefore, $T_{\Pi_n''}^\infty(\emptyset) \subseteq T_{\Pi_n^I}^\infty(\emptyset)$.

- $T_{\Pi_n^I}^\infty(\emptyset) \subseteq T_{\Pi_n''}^\infty(\emptyset)$. We first show for any variable x , $x \in T_{\Pi_n^I}^\infty(\emptyset)$ implies $x \in T_{\Pi_n''}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n^I}^1(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n$, $\text{var}(B_1) = \emptyset$ and $I \models B_1$. It follows that $x \leftarrow B_1 \in \Pi_n''$ and $x \leftarrow \in \Pi_n''$. So $x \in T_{\Pi_n''}^\infty(\emptyset)$. Let $k > 1$ and assume for all $i < k$, $x \in T_{\Pi_n^I}^i(\emptyset)$ implies $x \in T_{\Pi_n''}^\infty(\emptyset)$. Suppose $x \in T_{\Pi_n^I}^k(\emptyset)$, then $\exists x \leftarrow B_1 \in \Pi_n$ s.t. $x \leftarrow \text{var}(B_1) \in \Pi_n^I$, $\text{var}(B_1) \neq \emptyset$, $I \models B_1 \setminus \text{var}(B_1)$ and $T_{\Pi_n^I}^{k-1}(\emptyset) \models \text{var}(B_1)$. By induction hypothesis, $T_{\Pi_n''}^\infty(\emptyset) \models \text{var}(B_1)$, i.e., $I \models \text{var}(B_1)$. Now $I \models B_1$ since $I \models B_1 \setminus \text{var}(B_1)$ and $I \models \text{var}(B_1)$, hence $I \models B_1$. Observe that if $H = x$ and $B_1 = B$ then $x \leftarrow B' \in \Pi_n''$, otherwise $x \leftarrow B_1 \in \Pi_n''$. In both cases $I \models x$ since I is an answer set of Π_n'' and it must be closed under every rule of Π_n'' . Consequently, $x \in T_{\Pi_n''}^\infty(\emptyset)$ implies $x \in T_{\Pi_n^I}^\infty(\emptyset)$. It remains to show $\perp \notin T_{\Pi_n''}^\infty(\emptyset)$. Assume $\perp \in T_{\Pi_n''}^\infty(\emptyset)$, then $\exists \perp \leftarrow B_1$ in $F^+(\Pi_n)$ s.t. $\perp \leftarrow \in \Pi_n''$ and $I \models B_1$. Notice that $\text{var}(B_1) = \emptyset$ since Π_n is almost pure. Furthermore, $\perp \leftarrow B_1$ must be in Π_n'' , therefore $I \models \perp$ since $I \models B_1$. However, this contradicts the fact that I is an answer set of Π_n'' . Therefore $\perp \notin T_{\Pi_n''}^\infty(\emptyset)$, and hence $T_{\Pi_n^I}^\infty(\emptyset) \subseteq T_{\Pi_n''}^\infty(\emptyset)$.

Consequently, Π_n'' is an almost pure PARITY_n program with $m - 1$ non-pure rules. By induction hypothesis, there is a pure PARITY_n program Π_n' with $|\Pi_n'| \leq |\Pi_n''| \leq |\Pi_n|$. $\square$

4.4 The Main Results

The main lemma below easily follows from Proposition 4.1 and 4.2.

Lemma 4.5 (Main Lemma). *Let Π_n be a PARITY_n program. Then there is a PARITY_n program Π_n' s.t. Π_n' is equivalent to $\text{Comp}(\Pi_n')$ and $|\Pi_n'| \leq |\Pi_n|$.*

Theorem 4.1 ($\text{PARITY} \notin \text{Poly-CP}$). *PARITY has no polynomial size CP programs.*

Proof. Assume the contrary that there is a sequence of programs $\{\Pi_n\}$ in CP which represents PARITY , and $|\Pi_n|$ is bounded by a polynomial $p(n)$. By Lemma 4.5, there is a sequence of completion-equivalent PARITY programs $\{\Pi_n'\}$ in which $|\Pi_n'|$ is also bounded by the polynomial $p(n)$. By Proposition 3.1, $\{\Pi_n'\}$ represents a language in AC^0 . This contradicts $\text{PARITY} \notin \text{AC}^0$. $\square$

Corollary 4.1. *PARITY separates PF from CP.*




Figure 2: A Succinctness Picture

Corollary 4.2. *Suppose $P \not\subseteq NC^1/\text{poly}$. Then CP and PF are succinctly incompatible.*

5 Discussion and Some More Results

Interestingly, our main result may at first appear counter-intuitive: the P-complete problem PATH has Poly-CP representations, while this does not hold for an “easy” problem PARITY. Actually, there is no contradiction. As noted in [1, 8], a *complete* problem in a complexity class can be represented in a formalism $\mathcal{C}$, *does not* imply that *all* problems in that class can be represented in $\mathcal{C}$.

Generally speaking, the research of succinctness [17, 7, 19, 13] gives us a deeper understanding about KR formalisms, for it reveals their (in)abilities of concisely representing different problems under the condition that the encoded models are the *same*. In terms of the theory of computation, succinctness essentially concerns with the computational power of different formalisms (i.e., models of computation). This is particularly interesting if the formalisms are *equally expressive* and share the same reasoning complexity. E.g., logic programs with *cardinality constraints* and *choice rules* (CC, without classic negation $\neg$) [32], (*simple*) *definite causal theories* (S/DT) [16] and *two-valued* programs (TV) [27] are as expressive as PF and NP-complete for consistency checking. But they have a non-trivial succinctness picture, see Fig. 2.

Besides the theoretical interests, succinctness also tells us something like “which for what is the best” in choosing KR formalisms for a given application. E.g., one should choose ASP instead of SAT if the application involves reasoning about PATH or Transitive Closure⁵, because the former provides compact representations to avoid unnecessary overload. Recall that from the complexity viewpoint, even *one* extra variable may *double* the search space for intractable problems.

In the following we shall briefly discuss some succinctness results illustrated

⁵An NL-complete problem. It is believed that $NL \not\subseteq NC^1/\text{Poly}$.

in Fig. 2, note that all mentioned formalisms have the same expressive power and same reasoning complexity.

5.1 Logic Programs with Cardinality Constraints (CC)

Simply speaking, CC extends normal programs (LP) with so-called *cardinality constraints* and *choice rules* [32]. A *choice rule*

$$\{x\} \leftarrow \quad (8)$$

has two answer sets $\{x\}$ and $\emptyset$, i.e., same as $x \leftarrow \text{not not } x$. Moreover, a choice rule $\{x_1, \dots, x_n\} \leftarrow$ produces 2^n answer sets, i.e., all subsets of $\{x_1, \dots, x_n\}$. A *cardinality constraint* is an expression of the form

$$l \leq B \leq u \quad (9)$$

in which B is a finite set of rule elements of the form x or $\text{not } x$, and integer l (resp. u) is the lower (resp. upper) bound on B . In this paper we assume the magnitude of l (and u) is polynomially bounded by n .

Intuitively, a set of variables I satisfies (9), if the number of satisfied rule elements in B fulfills the related bounds. E.g., $\{x_1\}$ satisfies $1 \leq \{x_1, x_2, x_3\} \leq 1$ but not $2 \leq \{x_1, x_2, x_3\} \leq 3$, while $\{x_2, x_3\}$ satisfies the latter. Informally, we may think of (9) as a special kind of rule element, and the answer set semantics is defined accordingly.

The following is a PARITY_3 program in CC:

$$\begin{aligned} \{x_1, x_2, x_3\} &\leftarrow, \\ \perp &\leftarrow 0 \leq \{x_1, x_2, x_3\} \leq 0, \\ \perp &\leftarrow 2 \leq \{x_1, x_2, x_3\} \leq 2, \end{aligned} \quad (10)$$

Clearly, the pattern applies to all PARITY_n and the program grows linearly. We define the size of a CC program to be the number of cardinality constraints occur in it.

Theorem 5.1 ($\text{PARITY} \in \text{Poly-CC}$). *PARITY has polynomial size programs in CC.*

An equivalent translation from CC to NLP was presented in [12], however, the translation may involve exponential size blowup, since every cardinality constraint is simply converted to a formula via a brute force enumeration. In fact, such a translation can be reduced to be polynomial by adopting a non-trivial, sophisticated encoding for so-called *threshold functions*⁶. Therefore, we have:

Theorem 5.2. *NLP is at least as succinct as CC.*

⁶E.g., see Chapter 2 of [31].

5.2 Definite Causal Theories (DT)

A variable x or negated variable $\neg x$ is called a *literal*. A *definite (causal) theory* D_n on *signature* $\{x_1, \dots, x_n\}$ is a finite set of (causal) rules of the form

$$H \Leftarrow G \quad (11)$$

in which H is either a literal or $\perp$, and G is a propositional formula. If every G is a conjunction of variables or negated variables, then D_n is called *simple* (SDT)⁷.

The *reduct* D_n^I of D_n w.r.t. a set of variables I , is the set of the heads H of all rules in D_n whose bodies G are satisfied by I . Say I is a *model* of D_n if I is the unique model of D_n^I . The following theory:

$$x \Leftarrow x, \quad \neg x \Leftarrow \neg x \quad (12)$$

has two models $\{x\}$ and $\emptyset$, which is equivalent to program $x \leftarrow \text{not not } x$ or $\{x\} \leftarrow$.

If a definite theory D_n is simple, then its size $|D_n|$ is defined as the number of rules in it, otherwise $|D_n|$ is the number of connectives in it. It is well-known that D_n is equivalent to its (*literal*) completion $\text{Comp}(D_n)$, in which $\text{Comp}(D_n)$ is similarly defined as for logic programs [30, 16]. It means that definite theories are fragments of PF, i.e., $\text{DT} \leq \text{PF}$. Therefore, the problems that can be represented by Poly-DT are in NC^1/poly as well. Moreover, the completion of a simple definite theory is also a constant depth, unbounded fan-in circuit whose size is polynomially bounded. By a proof similar to that of Theorem 4.1, we have the following theorem:

Theorem 5.3 (PARITY $\notin$ Poly-SDT). *PARITY has no polynomial size theories in SDT.*

Consider the (non-simple) causal theory (13) for PARITY₂, where the body of the last rule is the negation of a PARITY₂ formula:

$$\begin{aligned} x_1 &\Leftarrow x_1, & \neg x_1 &\Leftarrow \neg x_1, \\ x_2 &\Leftarrow x_2, & \neg x_2 &\Leftarrow \neg x_2, \\ \perp &\Leftarrow \neg((x_1 \wedge \neg x_2) \vee (\neg x_2 \wedge x_1)). \end{aligned} \quad (13)$$

Recall that PARITY have polynomial formulas in PF, therefore it is not hard to see we can have polynomial DT theory for PARITY by the above pattern.

Theorem 5.4 (PARITY $\in$ Poly-DT). *PARITY has polynomial size theories in DT.*

Since PATH is P-complete [28], therefore if PATH has polynomial representations in Poly-DT, then $\text{P} \subseteq \text{NC}^1/\text{poly}$, which is believed impossible.

Theorem 5.5 (PATH $\notin$ Poly-DT). *Suppose $\text{P} \not\subseteq \text{NC}^1/\text{poly}$. Then PATH has no polynomial size definite theories.*

⁷SDT is originally named as *Objective Programs* in [30].

By the fact that PATH has polynomial size CP programs, we have:

Corollary 5.1. *Suppose $P \not\subseteq NC^1/\text{poly}$. Then CP and DT are succinctly incompatible.*

It is worth to point out that some difficulties observed in the literature could be nicely explained by the above succinctness results. E.g., DT has been observed hard to concisely encode Transitive Closure (TC) [16, 9]. Recall that Poly-DT represents problems in NC^1/Poly , and TC is a problem in NC^2/poly [18], a class widely believed strictly contains NC^1/poly . So unless the two classes coincide, TC has no polynomial size definite theories.

5.3 Two-Valued Logic Programs (TV)

A (two-valued) program [27] Π_n on signature $\{x_1, \dots, x_n\}$ is a finite set of (two-valued) rules of the form:

$$H \leftarrow B : G \quad (14)$$

in which $B \cup \{H\}$ is a finite set of literals and G is a formula. The *reduct* Π_n^I of Π_n w.r.t. a set of variables I , is the set of rules

$$H \leftarrow B \quad (15)$$

from Π_n s.t. I satisfies G . A set of literals J is *closed* under rule (15) if $H \in J$ whenever $B \subseteq J$. We say I is a *model* of Π_n if I is the *unique* model of the minimal closure J under every rule of Π_n^I . The following program Π_2 in TV

$$x \leftarrow: x, \quad \neg x \leftarrow: \neg x \quad (16)$$

has two models $\{x\}$ and $\emptyset$, which is equivalent to (12).

The following observations were pointed out in [27]. A formula ϕ_n can be rewritten in TV ($i \in \{1, \dots, n\}$)⁸:

$$x_i \leftarrow: x_i, \quad \neg x_i \leftarrow: \neg x_i, \quad \perp \leftarrow: \neg \phi_n. \quad (17)$$

A causal rule $H \Leftarrow G$ can be equivalently rewritten as $H \leftarrow: G$. Moreover, to equivalently rewrite a CP program Π_n , each rule:

$$H \leftarrow u_1, \dots, u_j, \quad \text{not } y_{j+1}, \dots, \text{not } y_m, \\ \text{not not } z_{m+1}, \dots, \text{not not } z_k \quad (18)$$

can be translated as:

$$H \leftarrow u_1, \dots, u_j : \neg y_{j+1} \wedge \dots \neg y_m \wedge z_{m+1} \wedge \dots z_k \quad (19)$$

and add $\neg x \leftarrow: \neg x$ for every $x \in \text{var}(\Pi_n)$. All together, we have:

Theorem 5.6. *Two valued programs are strictly more succinct than: (i) propositional formulas and definite theories, if $P \not\subseteq NC^1/\text{poly}$; (ii) canonical programs.*

⁸ $\perp \leftarrow: \neg \phi_n$ is a shorthand of $x_1 \leftarrow: \neg \phi_n, \neg x_1 \leftarrow: \neg \phi_n$.

6 Conclusions

The main result of the paper is that the PARITY problem separates PF from CP, i.e., PARITY has no polynomial size CP programs, but has polynomial size PF formulas. Together with Lifschitz and Razborov’s separation result, i.e., there exists a problem separates CP from PF (assuming $P \not\subseteq NC^1/\text{poly}$), we conclude that the two well-known KR formalisms are succinctly incomparable. In other words, if we consider CP and PF as two different models of computation, the above result just states that they are incomparable in terms of computational power. We also give a non-trivial succinctness picture on a family of logic program classes which possess the same expressive power and same reasoning complexity as PF.

In future work, we plan to investigate some missing connections in Fig. 2, e.g., we conjecture that there is a problem separates NLP from CP, SDT and CP are succinctly incomparable.

Acknowledgement

We are grateful to the anonymous reviewers for their valuable comments. Thanks to Shiguang Feng, Yan Zhang, Jiankun He, Guangrui Dang and Xiaolong Liang for their helpful discussions. The research was partially supported by NSFC Grant 61272059, MOE Grant 11JJD720020, NSSFC Grant 13&ZD186, 14CZX058 and the Fundamental Research Funds for the Central Universities Grant 1409025.

References

- [1] Serge Abiteboul, Richard Hull, and Victor Vianu. *Foundations of Databases*. Addison-Wesley, 1995.
- [2] K. R. Apt, H. A. Blair, and A. Walker. Towards a theory of declarative knowledge. In J. Minker, editor, *Foundations of Deductive Databases and Logic Programming*, pages 89–148. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 1988.
- [3] Sanjeev Arora and Boaz Barak. *Computational Complexity: A Modern Approach*. Cambridge University Press, 2009.
- [4] Armin Biere, Marijn Heule, Hans van Maaren, and Toby Walsh, editors. *Handbook of Satisfiability*, volume 185 of *Frontiers in Artificial Intelligence and Applications*. IOS Press, 2009.
- [5] Gerhard Brewka, Thomas Eiter, and Miroslaw Truszczyński. Answer set programming at a glance. *Communications of the ACM*, 54(12):92–103, 2011.
- [6] Keith L. Clark. Negation as failure. In H. Gallaire and J. Minker, editors, *Logic and Data Bases*, pages 292–322, New York, 1978. Plenum Press.

- [7] Sylvie Coste-Marquis, Jérôme Lang, Paolo Liberatore, and Pierre Marquis. Expressive power and succinctness of propositional languages for preference representation. In *Proceedings of the Ninth International Conference on Principles of Knowledge Representation and Reasoning*, pages 203–212. AAAI Press, 2004.
- [8] Evgeny Dantsin, Thomas Eiter, Georg Gottlob, and Andrei Voronkov. Complexity and expressive power of logic programming. *ACM Computing Surveys*, 33(3):374–425, September 2001.
- [9] Semra Doğandağ, Paolo Ferraris, and Vladimir Lifschitz. Almost definite causal theories. In Vladimir Lifschitz and Ilkka Niemelä, editors, *Logic Programming and Nonmonotonic Reasoning*, volume 2923 of *Lecture Notes in Computer Science*, pages 74–86. Springer Berlin Heidelberg, 2004.
- [10] Esra Erdem and Vladimir Lifschitz. Tight logic programs. *Theory and Practice of Logic Programming*, 3(4):499–518, July 2003.
- [11] François Fages. Consistency of clark’s completion and existence of stable models. *Journal of Methods of Logic in Computer Science*, 1:51–60, 1994.
- [12] Paolo Ferraris and Vladimir Lifschitz. Weight constraints as nested expressions. *Theory Pract. Log. Program.*, 5(1-2):45–74, January 2005.
- [13] Tim French, Wiebe van der Hoek, Petar Iliev, and Barteld P. Kooi. On the succinctness of some modal logics. *Artificial Intelligence*, 197:56–85, 2013.
- [14] Merrick L. Furst, James B. Saxe, and Michael Sipser. Parity, circuits, and the polynomial-time hierarchy. *Mathematical Systems Theory*, 17(1):13–27, 1984.
- [15] Michael Gelfond and Vladimir Lifschitz. The stable model semantics for logic programming. In Kowalski R. and Bowen K., editors, *Proceedings of International Logic Programming Conference and Symposium*, pages 1070–1080. MIT Press, 1988.
- [16] Enrico Giunchiglia, Joohyung Lee, Vladimir Lifschitz, Norman McCain, Hudson Turner, and Joohyung Lee Vladimir Lifschitz. Nonmonotonic causal theories. *Artificial Intelligence*, 153(1-2):49–104, 2004.
- [17] Goran Gogic, Henry A. Kautz, Christos H. Papadimitriou, and Bart Selman. The comparative linguistics of knowledge representation. In *Proceedings of the Fourteenth International Joint Conference on Artificial Intelligence*, pages 862–869. Morgan Kaufmann Publishers Inc., 1995.
- [18] Raymond Greenlaw, H. James Hoover, and Walter L. Ruzzo. *Limits to parallel computation: P-completeness theory*. Oxford University Press, 1995.

- [19] Martin Grohe and Nicole Schweikardt. The succinctness of first-order logic on linear orders. *Logical Methods in Computer Science*, 1(1), 2005.
- [20] Johan Hastad. Almost optimal lower bounds for small depth circuits. In *Proceedings of the eighteenth annual ACM symposium on Theory of computing*, STOC '86, pages 6–20, New York, NY, USA, 1986. ACM.
- [21] Stasys Jukna. *Boolean Function Complexity - Advances and Frontiers*, volume 27 of *Algorithms and combinatorics*. Springer, 2012.
- [22] Joohyung Lee. A model-theoretic counterpart of loop formulas. In *Proceedings of the 19th international joint conference on Artificial intelligence*, pages 503–508. Morgan Kaufmann Publishers Inc., 2005.
- [23] Joohyung Lee and Vladimir Lifschitz. Loop formulas for disjunctive logic programs. In Catuscia Palamidessi, editor, *Logic Programming*, volume 2916 of *Lecture Notes in Computer Science*, pages 451–465. Springer Berlin Heidelberg, 2003.
- [24] Joohyung Lee, Vladimir Lifschitz, and Fangkai Yang. Action language $\mathcal{BC}$: Preliminary report. In *Proceedings of the 23rd International Joint Conference on Artificial Intelligence*, pages 983–989. AAAI Press, 2013.
- [25] Vladimir Lifschitz. Nested expressions in logic programs. *Annals of Mathematics and Artificial Intelligence*, 25:369–389, 1999.
- [26] Vladimir Lifschitz. What is answer set programming? In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 1594–1597. MIT Press, 2008.
- [27] Vladimir Lifschitz. Two-valued logic programs. In *Technical Communications of the 28th International Conference on Logic Programming*, pages 259–266. Schloss Dagstuhl - Leibniz-Zentrum fuer Informatik, 2012.
- [28] Vladimir Lifschitz and Alexander Razborov. Why are there so many loop formulas? *ACM Transactions on Computational Logic*, 7(2):261–268, April 2006.
- [29] Fangzhen Lin and Yuting Zhao. ASSAT: computing answer sets of a logic program by SAT solvers. *Artificial Intelligence*, 157(1 - 2):115 – 137, 2004.
- [30] Norman McCain. *Causality in Commonsense Reasoning about Actions*. PhD thesis, University of Texas at Austin, 1997.
- [31] John E Savage. *Models of computation*. Exploring the Power of Computing. Addison-Wesley, 1998.

- [32] Patrik Simons, Ilkka Niemelä, and Timo Soininen. Extending and implementing the stable model semantics. *Artificial Intelligence*, 138(1-2):181–234, 2002.
- [33] Jia-Huai You, Li-Yan Yuan, and Mingyi Zhang. On the equivalence between answer sets and models of completion for nested logic programs. In *Proceedings of the 18th international joint conference on Artificial intelligence*, pages 859–864. Morgan Kaufmann Publishers Inc., 2003.